

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date
18 March 2004 (18.03.2004)

PCT

(10) International Publication Number
WO 2004/023611 A1

(51) International Patent Classification?: H01S 1/02, 3/094 (74) Agent: GRANLEESE, Rhian, Jane; Marks & Clerk, 57-60 Lincolns Inn Fields, London WC2A 3LS (GB).

(21) International Application Number:

PCT/GB2003/003871

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(22) International Filing Date:

4 September 2003 (04.09.2003)

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(25) Filing Language:

English

(26) Publication Language:


English

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: COHERENT THZ Emitter WITH DC POWER REDUCING RESISTOR



WO 2004/023611 A1

(57) Abstract: An emitter for emitting radiation in a first range of frequencies comprising: a photoconductive material (11); and first and second contact elements (12, 13, 14) separated by a photoconducting gap provided by said photoconducting material (11), for applying a bias across said photoconducting gap, wherein at least one of said first and second contact elements (12, 13, 14) comprises a resistive element (14) for restricting current flow between said first and second contact elements in a second range of frequencies lower than the first range of frequencies.